

Datacard® CP60™ Plus Card Printer



Delivering the fastest speeds in the Datacard portfolio, the CP60 Plus card printer maximizes productivity for brilliant, one- or two-sided secure IDs and casino/loyalty cards.

High-impact speed and versatility

Choose the Datacard® CP60™ Plus card printer for outstanding speed and superior operational versatility. This fast printer helps maximize productivity, delivering up to 190 full-color, one-sided cards or up to 1,000 single-color, one-sided cards per hour. The CP60 Plus card printer also offers two-sided printing and many other card personalization capabilities. All of which make it ideal for printing secure IDs for corporate and education environments, as well as loyalty cards and VIP cards for casinos. It is also optimized to work with Datacard® IDCentre™ identification software and capture solutions, as part of a fully integrated system.

Smart features for multiple technologies

- Smart card, proximity card and magnetic stripe options support multi-technology photo IDs as well as cards for loyalty, retail and membership programs.
- Connectivity options include USB and built-in Ethernet for convenient network access.
- The innovative printer driver provides message prompts, color image previews and online user help from the LCD panel.
- Exclusive Advanced Image Technology™ delivers true edge-to-edge printing and sharp image quality.



Datacard Group
SECURE ID AND CARD PERSONALIZATION SOLUTIONS

Datacard® CP60™ Plus Card Printer

Quick-change supplies switch out in seconds

100- or 200-card input hopper

Front-facing output hopper saves space



Standard LCD panel offers at-a-glance print status

Standard Ethernet and USB connectivity

The CP60 Plus card printer is an ideal choice for issuing corporate and education IDs, casino/loyalty cards and more.

Standard features

One- or two-sided edge-to-edge printing
Continuous-tone for full-color or black-and-white photos
Alphanumeric text, logos and digitized signatures
Variety of bar codes and background patterns
Automatic printer settings and offsets, automatic ribbon identification, validation and low ribbon warning
Full-color print speed of up to 190 cards per hour (one-sided) and up to 155 cards per hour (two-sided) and monochrome print speed of up to 1,000 cards per hour (one-sided) and up to 450 cards per hour (two-sided)
Backlit LCD panel
Bi-directional USB supported on Microsoft® Windows® 2000 and XP operating systems
Ethernet 10/100 Base-T bi-directional networking supported on Windows 2000 and XP operating systems
Printer driver pooling supported on Windows 2000 and XP operating systems
Datacard® Open Platform printer driver for non-Windows platforms
Printer driver features user-adjustable image and color controls, stand-alone driver diagnostics, image and test card previewing, online user help and supply usage tab
Audible and visual message prompts on printer and PC
Automatic card feed
Operator-replaceable printhead
Continuous cleaning roller
Easy access components, including quick-change ribbon cartridges
Highly accessible card path
24-month standard depot printer and printhead warranty

Options

One- or two-sided printing
ISO magnetic stripe encoding (IAT; dual high-and low-coercivity; tracks 1, 2 and 3 for IAT)
Smart card options include contact and contactless all-in-one reader; contact station; Prox by HID; and iCLASS® by HID
Magnetic stripe and smart card field upgradeability
100- or 200-card input hopper
200-card output hopper
Locking input hopper
Kensington® security lock for printer
Soft-sided carrying case
Support for OpenCard data format
Clear card personalization
Input hopper empty alert

Specifications

Dimensions: L 21.5 in. x W 7.8 in. x H 9.5 in. to H 11.9 in. (54.6 cm x 19.8 cm x 24.1 cm to 30.2 cm)
Weight: less than 11 lbs. (5.3 kg) without supplies
Print resolution of 300 dots per inch, 256 shades
Electrical requirements of 100/120V, 50/60 Hz; or 220/240V, 50/60 Hz
Accepts ISO ID-1/CR-80 size cards measuring 3.370 in. x 2.125 in. (85.6 mm x 53.98 mm); accepts glossy-surfaced PVC cards; accepts clear cards; other core materials with PVC overlaminates are optional
Accepts card thickness from 0.009 to 0.055 in. (0.2286 mm to 1.397 mm)
Operates in temperatures from 60° to 95°F (15° to 35°C) and non-condensing humidity from 20% to 80%
Agency approvals: UL (safety); FCC CFR47, Part 15, subparts b and c, class A (FCC Emissions); RoHS (EU and China)

Datacard® Certified Supplies featuring Intelligent Supplies Technology™

Datacard Group sales channels are your exclusive source for Datacard® Certified Supplies. Datacard® CP Plus Series card printers require the use of Datacard Certified Supplies in order to print properly.

DatacardGroup

11111 Bren Road West
Minnetonka, MN 55343-9015
+1 952 933 1223
+1 952 931 0418 FAX
www.datacard.com

Datacard, CP60, IDCentre, Intelligent Supplies Technology and Advanced Imaging Technology are trademarks, registered trademarks and/or service marks of DataCard Corporation in the United States and/or other countries. Microsoft and Windows are registered trademarks of Microsoft Corporation. iCLASS is a registered trademark of HID Corporation. Kensington is a registered trademark of ACCO World Corporation. Names and logos on sample cards are fictitious. Any similarity to actual names, trademarks or tradenames is coincidental. Specifications subject to change without notice.

©2007 DataCard Corporation. All rights reserved.
DP7-9009